

PRO 50% TRUCK

➤ DESCRIPTION

Anti-freeze for direct application, formulated with ethylene glycol and a mixture of organic technology (OAT) corrosion-inhibitors, as well as anti-cavitation, anti-lime and anti-foam additives, designed to protect the various metals in latest generation internal combustion engine cooling circuits, including the aluminium and light alloys, thereby providing efficient protection for the engine, radiator, water pump and heavy cooling circuit. Long life.

PROQUISUR does not recommend mixing this product with other coolants since this can reduce quality.

➤ PHYSICAL AND CHEMICAL PROPERTIES

ASPECT	LIQUID
COLOUR	FLUORESCENT GREEN, PINK, YELLOW OR BLUE
ODOR	CHARACTERISTIC
pH at 20°C	8,5-10,0
DENSITY at 20°C	1,060 +/- 1.080 g/cm ³
SOLUBILITY IN WATER	100% SOLUBLE
FLASH POINT	NOT APPLICABLE
FREEZING POINT	-36°C +/- 1 °C
BOILING POINT	+110°C +/- 1 °C

➤ SPECIFICATIONS

BS 6580
ASTM D 3306 D6210
UNE 26.361.88/1
SAE J-1034
MIL Italy1415c NATO S-759 JIS K2234 KSM 2142
CUNA NC 956-16
EMPA FVV HEFT R 443 AFNOR R 15/601
CUMMIINS 3666132/85T82
MB 325.3 // MB 326.3
MAN 324 type SNF
MTU MTL5048
RENAULT TRUCKS 41-01-001/S type D
DETROIT DIESEL 7SE298
MACK 014GS17004 NAVISTAR B1 PACCAR 70214-A-010
JI CASE JIC 501 MASSEY C.C M 1130A
JOHN DEERE JDM HD24 VERSATILE 42M CHRYLER MS 7170
FORD ESE M97B18C/ESE M97B44A GM 1825M/1899M H.T
VOLVO TRUCKS 1286083/02
CATERPILLAR CCS KENWOTH R026-170-97
NEW HOLLAND WSN-M97B18-D PETERBILT 8502.002
FREIGHLINER 48-22880
LADA TTM VAZ 197.717.97
IVECO 55.5231

➤ USE

*Suitable for all vehicle types and makes.
Indicated for all types of cooling systems.*

➤ PRESENTATION

Available packaging 1L, 4L, 5L, 20L, 60L, 200L y 1000L.

