

DIMASYNT 5W30 RN 17

DESCRIPTION

100% synthetic lubricant, developed to extend the life of the current emission reduction systems in new generation diesel and gasoline vehicles of the RENAULT group, manufactured since 2018.

- ❖ Reduces deposit formation, protecting internal engine components from wear, and maintains cleanliness
- ❖ Allows to achieve long change intervals
- ❖ Its low content of sulphated ash allows the particulate filters (DPF) to reach the duration estimated by the manufacturer
- ❖ Anti-friction properties, which improves fuel consumption

PHYSICAL-CHEMICAL PROPERTIES

TIPE OF ANALYSIS	METHOD	RESULTS
Grade SAE	-----	5W30 C3
Viscosity at 40°C, cst	ASTM D-445	>65
Viscosity at 100°C, cst	ASTM D-445	9,3-12,5
TBN mgKOH/g	ASTM D-2896	>7,5
Viscosity index	ASTM D-2270	165
Freezing point min, °C	ASTM D-97	-36°C
Flash point min, °C	ASTM D-92	>220°C
Sulphated ash,% max, mass	ASTM D-874	0,8

USE

Especially recommended for high-performance RENAULT group passenger cars, both diesel and gasoline, with modern engines equipped with special particle filters. Lubricant compatible with DPF, SCR, catalytic converters and GPF.

DIMASOIL

AUTOMOTIVE CHEMICAL FLUIDS

SPECIFICATIONS

ACEA C3
RENAULT RN 17

PRESENTATION

Available packaging 1L, 4L, 5L, 25L, 60L, 204L y 1000L

PROQUISUR

PRO DIMASOIL arlo

Los valores de características típicas que figuran en el cuadro son valores medios dados a título indicativo y no constituyen una garantía.
Estos valores pueden ser modificados sin previo aviso.

PROQUISUR SL | P. I. La Salina, 26-27 | 14960 RUTE (Córdoba) SPAIN | Tel. (+34) 957 538 743 | www.proquisur.com