

## DIMATECH 15W40

### DESCRIPTION

High-quality synthetic lubricant specially developed to protect the engine from the formation of sludge caused by temperatures, contaminants and short distances.

Its most outstanding features are excellent wear protection and good engine cleanliness, as well as fuel economy.

1. Efficient sludge and deposit control, keeping the engine cleaner
2. Excellent wear protection
3. Ready to remove contaminants caused by short trips

### PHYSICOCHEMICAL PROPERTIES

TYPE D'ANALYSE	METHOD	RESULTS
SAE Grade	SAE J 300	10W40
Density at 15 °C g/mL		0,860-0,880
Viscosity at 100°C, cst	ASTM D-445	12,5-16,3
TBN, mg KOH/g	ASTM D-2896	>7,5
Viscosity index	ASTM D-2270	140
Freezing, °C	ASTM D-97	-30°C
Flash Point, min, °C	ASTM D-92	>210°C

### SPECIFICATIONS

API SP  
ACEA A3/B4  
MB 229.1  
RN 0700/0710  
VW 501.01/505.00

### PRESENTATION

**DIMASOIL**

AUTOMOTIVE CHEMICAL FLUIDS

*Packaging available 1L, 4L, 5L, 25L, 60L, 204L y 1000L*

**PROQUISUR**

**PRO DIMASOIL arlo**

Los valores de características típicas que figuran en el cuadro son valores medios dados a título indicativo y no constituyen una garantía.  
Estos valores pueden ser modificados sin previo aviso.

PROQUISUR SL | P. I. La Salina, 26-27 | 14960 RUTE (Córdoba) SPAIN | Tel. (+34) 957 538 743 | [www.proquisur.com](http://www.proquisur.com)