

## EXPERT 15W40 TDI SYNT

### DESCRIPTION

Synthetic lubricant for cars and light commercial vehicles with petrol or diesel engines from most vehicle manufacturers. It offers excellent engine cleanliness and complete engine protection due to the bases that are used. Its studied composition gives it a high resistance to wear, corrosion and oxidation. High detergency and dispersance levels allow for longer oil change intervals. Its high viscosity index allows excellent cold starts and contributes to fuel savings

- ❖ General engine protection and good cleaning of the same
- ❖ Prolonged oil change period
- ❖ Resistance to the formation of deposits and sludge
- ❖ High detergent power to neutralize the acids generated in combustion
- ❖ Very stable to evaporation

### PHYSICO-CHEMICAL PROPERTIES

TYPE OF ANALYSE	METHOD	RESULTS
<i>Grade SAE</i>	SAE J 300	15W40
<i>Density at 15°C Kg/L</i>	ASTM D-1298	0,870-0,880
<i>Viscosity at 100°C, cst</i>	ASTM D-445	12,5-16,3
<i>Viscosity index mín.</i>	ASTM D-2270	145
<i>TBN, mgKOH/g</i>	ASTM D-2896	>10
<i>Freezing point, °C</i>	ASTM D-97	-30°C
<i>Flash point, mín, °C</i>	ASTM D-92	>200°C
<i>Sulphated ash % wt</i>	ASTM D-874	<1,5

### SPECIFICATIONS

API SN/CF  
ACEA A3/B4  
MB 229.1

# **DIMASOIL**

AUTOMOTIVE CHEMICAL FLUIDS

VW 505.00

## **PRESENTATION**

Available Packaging 1L, 4L, 5L, 25L, 60L, 204L y 1000L

**PROQUISUR**

**PRO DIMASOIL arlo**

Los valores de características típicas que figuran en el cuadro son valores medios dados a título indicativo y no constituyen una garantía.  
Estos valores pueden ser modificados sin previo aviso.

PROQUISUR SL | P. I. La Salina, 26-27 | 14960 RUTE (Córdoba) SPAIN | Tel. (+34) 957 538 743 | [www.proquisur.com](http://www.proquisur.com)