

## EXPERT 20W50 SYNT

### DESCRIPTION

Multigrade synthetic lubricant for gasoline or diesel engines. Its formulation is focused on providing good operation at high temperatures, low lubricant consumption and low shear regardless of the use of the vehicle.

- ❖ General engine protection and good cleaning
- ❖ High detergent power to neutralize acids generated in combustion
- ❖ Excellent protection against wear, corrosion and oxidation
- ❖ Thermal stability, preventing sludge formation
- ❖ Improved cleaning of accumulated dirt due to its formulation with synthetic bases

### PHYSICO-CHEMICAL PROPERTIES

TYPE OF ANALYSE	METHOD	RESULTS
<i>Grade SAE</i>	SAE J 300	20W50
<i>Density at 15°C Kg/L</i>	ASTM D-1298	0,890-0,895
<i>Density at 100°C, cst</i>	ASTM D-445	16,3-21,9
<i>TBN, mgKOH/g</i>	ASTM D-2896	>10
<i>Viscosity index</i>	ASTM D-2270	120
<i>Freezing point, °C</i>	ASTM D-97	-30°C
<i>Flash point mín, °C</i>	ASTM D-92	>220°C
<i>Sulphated ashes, % wt</i>	ASTM D-874	<1,6
<i>Corrosion test Cu, 3h 100°C</i>	ASTM D-130	1A
<i>Foams Sec. I, II, III formation, mL</i>	ASTM D-892	10/50/10
<i>Foams Sec. I, II, III stability, mL</i>	ASTM D-892	0/0/0

### SPECIFICATIONS

API SN/CF  
ACEA A3/B4  
MB 229.1

# **DIMASOIL**

AUTOMOTIVE CHEMICAL FLUIDS

VW 505.00

## **PRESENTATION**

Available packaging 1L, 4L, 5L, 25L, 60L, 204L y 1000L

**PROQUISUR**

**PRO DIMASOIL arlo**

Los valores de características típicas que figuran en el cuadro son valores medios dados a título indicativo y no constituyen una garantía.  
Estos valores pueden ser modificados sin previo aviso.

PROQUISUR SL | P. I. La Salina, 26-27 | 14960 RUTE (Córdoba) SPAIN | Tel. (+34) 957 538 743 | [www.proquisur.com](http://www.proquisur.com)