

CLASS 0W20 TLV FULL SYNT

DESCRIPTION

100% synthetic lubricant of the latest generation and high performance, specially developed for Euro VI engines with fuel economy package (FEP1). Its formulation is low in SAPS.

0W20 TLV has been developed to meet the standards of Iveco's 18-1804 Classe TLV-LS specification.

- ❖ Excellent cleaning property, which favors the durability of the engine
- ❖ Offers total protection of the aftermarket system
- ❖ Excellent fuel economy thanks to its low viscosity. In addition to the reduction of CO2 emissions
- ❖ Exceptional viscosity at low temperature for better lubrication during start-up

PHYSICO-CHEMICAL PROPERTIES

TYPE OF ANALYSIS	METHOD	RESULTS
<i>Grade SAE</i>	SAE J 300	0W20
<i>Density at 15°C Kg/L</i>	ASTM D-1298	0,840-0,870
<i>Viscosity at 100°C, cst</i>	ASTM D-445	6,9-9,3
<i>TBN, mgKOH/g</i>	ASTM D-2896	>9
<i>Viscosity index mín.</i>	ASTM D-2270	>150
<i>Freezing point, °C</i>	ASTM D-97	-42°C
<i>Flash point, mín, °C</i>	ASTM D-92	>220°C

SPECIFICATIONS

TLV-LS IVECO 18-1804
DTFR 15C140 (EX MB 228.71)

PRESENTATION

Available packaging 5L, 25L, 60L, 204L y 1000L