

MAXIMUM 20W50

DESCRIPTION

Mineral lubricating oil specially formulated to meet diesel engines under high loads. Its studied composition gives it a high resistance to wear, corrosion and oxidation, and provides very high levels of detergency and dispersance, allowing longer oil change intervals. High-performance oil for heavy-duty diesel vehicles, including high-horsepower units, type S.H.P.D.

1. Long-lasting lubricant in service and high quality.
2. Anti-wear and anti-corrosive qualities, detergent and dispersant.
3. Keeps carbonaceous particles in suspension

PHYSICO-CHEMICAL PROPERTIES

| TYPE OF ANALYSIS | METHOD | RESULTS |
|-------------------------|-------------|-------------|
| SAE Grade | SAE J 300 | 20W50 |
| Density at 15°C, g/mL | ASTM D-1298 | 0,860-0,880 |
| Viscosity at 40°C, cst | ASTM D-445 | 130 |
| Viscosity at 100°C, cst | ASTM D-445 | 16,3-21,9 |
| TBN, mg KOH/g | ASTM D-2896 | >9.0 |
| Min. Viscosity Index | ASTM D-2270 | 120 |
| Freezing Point, °C | ASTM D-97 | -27°C |
| Flash Point, min, °C | ASTM D-92 | 220°C |

SPECS

API CI-4/SL
ACEA E7-22
ACEA A3/B4
Deutz DQC III-10
DTFR 15B110 (MB 229.3)
DETROIT DIESEL DCC 93K215

DIMASOIL

AUTOMOTIVE CHEMICAL FLUIDS

PRESENTATION

Available Packaging 5L, 25L, 60L, 204L y 1000L

PROQUISUR

PRO DIMASOIL arlo

Los valores de características típicas que figuran en el cuadro son valores medios dados a título indicativo y no constituyen una garantía.
Estos valores pueden ser modificados sin previo aviso.

PROQUISUR SL | P. I. La Salina, 26-27 | 14960 RUTE (Córdoba) SPAIN | Tel. (+34) 957 538 743 | www.proquisur.com