

## MAXIMUM 15W40 SYNT

### DESCRIPTION

*Specially formulated state-of-the-art lubricating oil with synthetic bases for diesel engines with exhaust gas recirculation (EGR). Its studied composition gives it a high resistance to wear, corrosion and oxidation, and offers very high levels of detergency and dispersance, allowing longer oil change intervals (up to 30,000 km). High performance oil for heavy-duty diesel vehicles, including high-horsepower units, type S.H.P.D.*

- 1. Long-lasting, high-quality lubricant in service*
- 2. Anti-wear and anti-corrosion qualities, detergents and dispersants*
- 3. Keeps carbon particles in suspension*
- 4. Compatible with all types of engines that use EGR and exceed the above specifications*

### PHYSICOCHEMICAL PROPERTIES

TYPE D'ANALYSE	METHOD	RESULTS
SAE Grade	SAE J 300	15W40
Density at 15°C, kg/l	ASTM D-1743	0,860-0,880
Viscosity at 100°C, cst	ASTM D-445	12,5-16,3
TBN, mgKOH/g	ASTM D-2896	>10,0
Freezing, °C	ASTM D-97	-32 °C
Flash Point, min, °C	ASTM D-92	>210°C

### SPECIFICATIONS

API CI-4  
ACEA A3/B4  
ACEA E7  
Deutz DQC III-18  
MB 229.1- MB 228.3  
MACK EO-N/MACK EO-M/MACK EO-M plus  
MAN M 3275-1  
DETROIT DIESEL DCC 93K215  
Renault TRUCKS RLD/RLD-2  
Scania LDF-2, LDF-3  
Volvo VDS-3  
CUMMINS CES 20076/77/78



AUTOMOTIVE CHEMICAL FLUIDS

*MTU Type 2  
IVECO-PEGASO  
CAT ECF-2*

## **PRESENTATION**

*Packaging available 5L, 25L, 60L, 204L y 1000L*

**PROQUISUR**

**PRO DIMASOIL arlo**

Los valores de características típicas que figuran en el cuadro son valores medios dados a título indicativo y no constituyen una garantía.  
Estos valores pueden ser modificados sin previo aviso.

PROQUISUR SL | P. I. La Salina, 26-27 | 14960 RUTE (Córdoba) SPAIN | Tel. (+34) 957 538 743 | [www.proquisur.com](http://www.proquisur.com)