

DIMASYNT 5W30 LONG LIFE

DESCRIPTION

100% synthetic lubricant, specially designed for recent vehicles of the VAG group (VOLKSWAGEN, AUDI, SKODA, and SEAT), equipped with engines that meet the Euro 4, 5 and 6 anti-pollution standards and that require a low oil content. in Sulphur, Phosphorus and Sulfated Ash (low SAPS). This product has been developed to prolong the useful life of current emission reduction systems and improve their performance.

- ❖ Reduces deposit formation, protecting internal engine components from wear and maintaining cleanliness
- ❖ Allows to achieve long oil change intervals (Long Life)
- ❖ Its low content of sulfated ash allows the particulate filters to reach the duration estimated by the manufacturer
- ❖ Anti-friction properties, which improves fuel consumption
- ❖ Perfect compatibility with post-treatment systems such as catalytic converters, SCR (Selective Catalytic Reduction) and DPF, in order to guarantee failure-free reliability of any gasoline and diesel engine of VAG group vehicles (VOLKSWAGEN, AUDI, SEAT and SKODA)

PHYSICAL-CHEMICAL PROPERTIES

| TYPE OF ANALYSIS | METHOD | RESULTS |
|--------------------------------|-------------|----------|
| <i>Grade SAE</i> | SAE J 300 | 5W30 |
| <i>Viscosity at 40°C, cst</i> | ASTM D-445 | >65 |
| <i>Viscosity at 100°C, cst</i> | ASTM D-445 | 9,3-12,5 |
| <i>TBN, mgKOH/g</i> | ASTM D-2896 | >6,5 |
| <i>ViscosityIndex</i> | ASTM D-2270 | 165 |
| <i>Freezing Point°C</i> | ASTM D-97 | -35°C |
| <i>Flash Point min, °C</i> | ASTM D-92 | >210°C |
| <i>SulphatedAshes % wt</i> | ASTM D-874 | 0,6 |

USE

Especially recommended for high-performance passenger cars, both diesel and gasoline, with modern engines equipped with special particle filters. Essential lubricant for vehicles that incorporate DFP / FAP filters in order to reach the duration estimated by the manufacturer.

SPECS

ACEA C3/C2
API SN
GM DEXOS 2
VW 502.00/505.00/505.01 (APPROVED UNDER VW STANDARD 505.00 AND VW 505.01)
MB 229.52
BMW Longlife- 04
JAGUAR LAND ROVER ST JLR.03.5004

PRESENTATION

Available packaging 1L, 4L, 5L, 25L, 60L, 204L y 1000L