

TECHNOSYNT 10W40

DESCRIPTION

State-of-the-art synthetic lubricant specially formulated to meet the vast majority of the most demanding modern specifications. Its studied composition gives it a high resistance against wear, corrosion and oxidation and provides it with very high levels of detergency and dispersance, allowing longer oil change intervals. Due to its low viscosity, it allows excellent cold starts and contributes to fuel savings (E.C.).

- ❖ Resistance to oil oxidation
- ❖ Facilitates cold starts due to its low viscosity
- ❖ Reduces friction

PHYSICAL-CHEMICAL PROPERTIES

TIPE OF ANALYSIS	METHOD	RESULTATS
<i>Grade SAE</i>	-----	10W40
<i>Viscosity at 40°C, cst</i>	ASTM D-1743	0,875
<i>Viscosity at 100°C, cst</i>	ASTM D-445	12,5-16,3
<i>TBN mgKOH/g</i>	ASTM D-2896	>9,5
<i>Viscosity index</i>	ASTM D-2270	150
<i>Freezing point min, °C</i>	ASTM D-97	-33°C
<i>Flash point min, °C</i>	ASTM D-92	>210°C
<i>Sulphated ash,% max, mass</i>	ASTM D-874	<1,6

USE

For all types of latest generation diesel and gasoline engines, high performance and competition regime, both in severe service and turbo-fueled.

SPECIFICATIONS

API SN/CF
ACEA A3/B4-12
MB 229.3
VW 502.00/505.00
RN 700/710

DIMASOIL

AUTOMOTIVE CHEMICAL FLUIDS

PRESENTATION

Available packaging 1L, 4L, 5L, 25L, 60L, 204L y 1000L

PROQUISUR

PRO DIMASOIL arlo

Los valores de características típicas que figuran en el cuadro son valores medios dados a título indicativo y no constituyen una garantía.
Estos valores pueden ser modificados sin previo aviso.

PROQUISUR SL | P. I. La Salina, 26-27 | 14960 RUTE (Córdoba) SPAIN | Tel. (+34) 957 538 743 | www.proquisur.com