

## EXPERT 15W40 TDI

### DESCRIPTION

State-of-the-art mineral lubricating oil specially formulated to meet the vast majority of the most demanding modern specifications. Its studied composition gives it a high resistance against wear, corrosion and oxidation and provides it with very high levels of detergency and dispersance, allowing longer oil change intervals (up to 30,000 km) Its high Viscosity Index allows excellent cold starts and contributes to fuel economy (EC).

### PHYSICAL-CHEMICAL PROPERTIES

TIPE OF ANALYSIS	METHOD	RESULTS
Grade SAE	-----	15W40 TDI
Viscosity at 40°C, cst	ASTM D-445	0,880
Viscosity at 100°C, cst	ASTM D-445	12,5-16,3
TBN mgKOH/g	ASTM D-2896	>7,5
Viscosity index	ASTM D-2270	135
Freezing point min, °C	ASTM D-97	-27°C
Flash point min, °C	ASTM D-92	>190°C
Sulphated ash,% max, mass	ASTM D-874	>1,5

### USE

For all types of diesel engines, especially those of Direct Injection, turbocharged, ect. Also recommended for gasoline engines that require long-lasting and demanding oils, ideal for multi-valve engines that require this degree of viscosity, turbocharged and especially those called GTI.

### SPECIFICATIONS

API SL/CF  
ACEA A3/B3-12  
Deutz DQC II-05  
MB 229.1  
VW 505.00

# **DIMASOIL**

AUTOMOTIVE CHEMICAL FLUIDS

## **PRESENTATION**

*Available packaging 1L, 4L, 5L, 25L, 60L, 204L y 1000L*

**PROQUISUR**

**PRO DIMASOIL arlo**

Los valores de características típicas que figuran en el cuadro son valores medios dados a título indicativo y no constituyen una garantía.  
Estos valores pueden ser modificados sin previo aviso.

PROQUISUR SL | P. I. La Salina, 26-27 | 14960 RUTE (Córdoba) SPAIN | Tel. (+34) 957 538 743 | [www.proquisur.com](http://www.proquisur.com)