

## EVOX 20W50

### DESCRIPTION

High performance mineral multigrade lubricant oil. Thanks to its formulation, it keeps the pressure hot, provides excellent anti-wear power and offers superior lubrication of the engine parts.

### PHYSICAL-CHEMICAL PROPERTIES

TIPE OF ANALYSIS	METHOD	RESULTS
<i>Grade SAE</i>	----	20W50
<i>Viscosity at 40°C, cst</i>	ASTM D-445	0,860-0,890
<i>Viscosity at 100°C, cst</i>	ASTM D-445	16,3-21,9
<i>TBN mgKOH/g</i>	ASTM D-2896	>7,0
<i>Viscosity index</i>	ASTM D-2270	120
<i>Freezing point min, °C</i>	ASTM D-97	-27°C
<i>Flash point min, °C</i>	ASTM D-92	>210°C
<i>Sulphated ash, % max, mass</i>	ASTM D-874	>1,5

### USE

*For all types of Diesel and Gasoline Engines subjected to very severe regimes. Especially recommended for supercharged Diesel Engines with widely spaced oil changes. Heavy transport, TIR, Public Works, etc.*

### SPECIFICATIONS

API CF-4/SF  
ACEA E2  
MB 228.1  
MAN 271

### PRESENTATION

Available packaging 1L, 4L, 5L, 25L, 60L, 204L y 1000L