

DIMASYNT 0W20 VCC



DESCRIPTION

Premium quality 100% synthetic lubricant offering excellent cold start characteristics and optimal wear protection. This product is recommended for the lubrication of Volvo Drive-E engines, when the manufacturer recommends the use of an approved Volvo VCC RBS0-2AE and SAE 0W-20 lubricant. It has exceptional fuel saving properties (Fuel Economy)

- ❖ Reduction of environmental impact
- ❖ It has detergent and dispersant additives that keeps the engine parts in an excellent state of cleanliness.
- ❖ Easy cold start, even at very low temperatures
- ❖ Reduces friction

PHYSICAL-CHEMICAL PROPERTIES

TYPE OF ANALYSIS	METHOD	RESULTS
SAE Grade	SAE J 300	0W20
Viscosity at 40°C, cst	ASTM D-445	>40
Viscosity at 100°C, cst	ASTM D-445	6,9-9,3
Viscosity index	ASTM D-2270	>160
Freezing point min, °C	ASTM D-97	-42°C
Flash point min, °C	ASTM D-92	>220°C
Base Number, mg KOH/g	ASTM D-2896	≥7,0
Sulphated ashes, %	ASTM D-874	0,78

SPECS

API SN
ACEA C5
VOLVO CAR CORPORATION VCC RBS0-2AE (Approved under VOLVO CAR CORPORATION)
PSA B71 2010

DIMASOIL

AUTOMOTIVE CHEMICAL FLUIDS

PRESENTATION

Available packaging 1L, 4L, 5L, 25L, 60L, 204L y 1000L

PROQUISUR

PRO DIMASOIL arlo

Los valores de características típicas que figuran en el cuadro son valores medios dados a título indicativo y no constituyen una garantía.
Estos valores pueden ser modificados sin previo aviso.

PROQUISUR SL | P. I. La Salina, 26-27 | 14960 RUTE (Córdoba) SPAIN | Tel. (+34) 957 538 743 | www.proquisur.com