

DIMADEX ATF 236.17

DESCRIPTION AND QUALITIES

Automatic transmission fluid formulated with 100% synthetic oils developed for the latest generation of Mercedes-Benz 9-speed automatic transmission models of the execution 725.0/1.

Can be used where MB-236.16 is recommended

- ❖ Excellent resistance to oxidation and foaming.
- ❖ Protects against deposit formation, extending transmission life.
- ❖ Extremely fluid at low temperatures, protecting the transmission at the time of vehicle start-up as well as operation in very low temperatures

PHYSICAL-CHEMICAL PROPERTIES

TYPE OF ANALYSIS	METHOD	RESULTS
<i>Colour/ Appearance</i>	D-1500	Ambar/Brillante
<i>Viscosity at 40°C, cst</i>	ASTM D-445	>17
<i>Viscosity at 100°C, cst</i>	ASTM D-445	4-5
<i>Density 15°C</i>	ASTM D-1298	0,84
<i>Viscosity index mín.</i>	ASTM D-2270	>160
<i>Flash point</i>	ASTM D-92	>180°C

SPECIFICATIONS

MB 236.17 (retroaplicable a MB 236.16)

PRESENTATION

Available packaing 500 ML, 1L, 4L, 5L, 25L, 60L, 204L y 1000L