

DIMASYNT 5W40 VW 511.00

DESCRIPTION

High quality 100% synthetic lubricant developed for latest generation vehicles equipped with Gasoline and direct injection turbo diesel engines that meet EURO 4, 5 or 6 and ACEA C3 regulations.

- Excellent cold start, allowing rapid circulation at low temperatures.
- Reduces the emission of greenhouse gases.
- High detergent, dispersant and antioxidant capacity, keeping the engine in a perfect state of cleanliness, minimizing the formation of sludge at the bottom of the crankcase and preventing filter clogging
- VW specification 511.00, provides shear strength

PHYSICAL-CHEMICAL PROPERTIES

TYPE OF ANALISIS	METHOD	RESULTS
<i>Grade SAE</i>	-----	5W40 C3
<i>Viscosity 40°C, cst</i>	ASTM D-445	>70
<i>Viscosity a 100°C, cst</i>	ASTM D-445	12,5-16,3
<i>TBN, mg KOH/g</i>	ASTM D-2896	>7,0
<i>Viscosity index</i>	ASTM D-2270	>165
<i>Freezing point, °C</i>	ASTM D-97	-35°C
<i>Flash point, mín, °C</i>	ASTM D-92	>220°C
<i>Sulphated ash % masa</i>	ASTM D-874	0,6

SPECIFICACIONES

API SN
ACEA C3
BMW LL-04
VW 511.00
MB 229.51/52/31/226.5
GM dexos 2
Porsche C40
RENAULT 0700/0710

DIMASOIL

AUTOMOTIVE CHEMICAL FLUIDS

PRESENTATION

Available packaging 1L, 4L, 5L, 25L, 60L, 204L y 1000L

PROQUISUR

PRO DIMASOIL arlo

Los valores de características típicas que figuran en el cuadro son valores medios dados a título indicativo y no constituyen una garantía.
Estos valores pueden ser modificados sin previo aviso.

PROQUISUR SL | P. I. La Salina, 26-27 | 14960 RUTE (Córdoba) SPAIN | Tel. (+34) 957 538 743 | www.proquisur.com